

# LSC1212DE

## ELECTRIC SCISSOR LIFT



Comply with CE standard

### ► Security and Intelligence

- Intelligent control system, real-time monitoring of equipment status;
- Multiple security protection to ensure personnel safety;
- Intelligent charging system to extend battery service life.

### ► Easy to Control

- Drivable at full height to improve working efficiency;
- The proportion drops and the descent moves smoothly;
- Forklift pocket, easy to load, unload and transport.

### ► Maintenance Friendly

- Self-lubricating sleeve;
- Swing-out tray on both sides, easy maintenance;
- Fault code indication to facilitate troubleshooting.

### Standard Features

- Standard longitudinal forklift sprocket hole
- Standard lateral forklift sprocket hole
- Adjustable extension platform
- Active pothole protection
- All motion alarm
- Emergency lowering system
- Drop anti-clip function
- Side anti-collision function

- Charging protection system
- Emergency stop button
- Proportional control
- Acousto-optic warning lights
- Drivable at full height
- Folding guardrails
- Over tilt protective system



Sales hotline : (+86) 511- 80960018

National service hotline : 4008-899-856

[www.liugong.com](http://www.liugong.com)

We reserve the right to change the plan and parameters without informing the users as Liugong products are constantly updated and improved.

The product configuration and appearance in the photo are different from the actual model which should be subject to the actual product.

Liugong series logo in this brochure is a registered trademark of Guangxi Liugong Group Company, which has been legally authorized to use by us. Others are not allowed to use it without authorization.

# LSC1212DE >>>

### Specifications

Item	Unit	LSC1212DE
Size		
A - Max.Work Height	m	14
B - Max.Platform Height	m	12
C - Min.Platform Height	m	1.47
D - Platform Length	m	2.28
E - Platform Width	m	1.15
F - Max.Platform Extension Length	m	0.9
G - Overall Length	m	2.49
H - Overall Length(Without Ladder)	m	2.29
I - Overall Width	m	1.19
J - Overall Height (Rails Up)	m	2.63
K - Overall Height (Rails Down)	m	2.07
L - Wheelbase	m	1.88
M- Ground Clearance (Stowed)	mm	100
N - Ground Clearance (Raised)	mm	20
Performance		
Rated Load on Working Platform	kg	320
Safe Working Load on Extended Platform	kg	120
Max. Occupants	/	2
Travel Speed (Stowed)	km/h	4
Travel Speed (Raised)	km/h	0.7
Turning Radius (Inside)	m	0
Turning Radius (Outside)	m	2.3
Up/Down Time	s	60/55
Max.Gradeability	/	25%
Max. Working Slope (Lateral/Vertical)	°	X1.5°/Y3°
Tire size	mm	381x127
Power		
Drive Motor	kW	1.5
Battery	/	300Ah
Charger	/	24V30A
Weight		
Total Weight	kg	3170

Swing-out Tray

Emergency Lowering System

Acousto-optic Warning Lights

Steering System

Extended Platform

Safety Overhaul Bracket

Folding Guardrails

Max.Gradeability 30%